[http://www.cartft.com/catalog/il/1313]





999.00 EUR

incl. 19% VAT, plus shipping

- 2x RS232!
- USB Host!
- Dual Core 900Mhz!
- 256MB RAM!

Support: RS232 Pinout | WinCE Mode | GUI GPS Link | Rear camera sensor | RS232 Pinout (CMO-Version) | SDK | Developer Notes

The CTFPND-6 is a 7" Touchscreen PND on Windows CE 6.0 basis with integrated GPS receiver and RS232 interfaces. Therefor the CTFPND-6 is the perfect plattform for your telematics application. The extra-high native resolution of 800x480 enables a perfect viewing quality.

The device is equipped with a FM transmitter,2x RS232, USB Host and video input. Optionally this device can be equipped with an external TMC receiver.

**Note:** This PND is an offer primarily meant for business and project customers. End consumers should only consider purchasing this device when they have appropriate experience.

## Hardware

CPU Flash ROM SDRAM TFT LCD Resolution Prima Dual Core 900Mhz 128MB NAND Flash (BGS type) 256 MB DDR-II 7" Touchscreen (Samsung, 24bit color) 800x480



## [CTFPND-6] 7" PND (2x RS232, USB-Host, FM, AV-IN, 800x480, 900Mhz, 256MB RAM) [Minimum order qty. 250 units]

[http://www.cartft.com/catalog/il/1313]

TMC

RS232

FM Transmitter

Speaker

Memory slot

**GPS** 

Video Input

Connector

Power
Weight
Dimensions
Software

Operating system

Navigation software

**Features** 

Lieferumfang



Optional

2x Integrated (TTL or 12V depending on adapter cable)

Integrated Integrated

SD/SDHC (up to 32GB, SanDisk recommended)

Integrated, SIRFstar III (20 channels)

2 AV inputs (Rear CAM support)

- SD extension box (optional)
- 2x Serial port
- USB slave
- Rear camera (3.55mm jack)
- AV-In (3.55mm jack)
- SD slot
- External IR (optional)
- USB Host
- Power socket DC
- 3.55mm stereo earphone jack
- Antenna socket for external GPS antenna (additional antenna not included)

12/24V DC (1.5A PMIC, Rebooting protection circuit)

368g

190 x 120 x 20 mm

MS Windows CE.NET 6.0 (core version)

Optional

- Generic RNDIS driver (installed)
- Compact .NET Framework 3.5 (installed)
- CTFPND-6 (7" PND)
- Mounting adapter
- 12/24V cigarette lighter adapter
- AC/DC-adapter
- 2x RS232 cable (TTL + 12V) [12V power source not included]
- Window suction mounting unit