



109.00 EUR
incl. 19% VAT, plus [shipping](#)



- VIA VX900H Chipset
- Support VIA Nano L2007 (65nm,FSB 800MHz,1.6GHz) processor
- Integrated Chrome9 HD DX9 Engine
- Integrated LVDS support 24-bit TFT LCD
- Support 1 x 32-bit PCI slot
- Support 2 x Serial ATA 2 Devices
- 2 * Gigabit LAN
- Support DC Fan
- VIA VT1705 HD Audio Codec with 6-Channel
- 170 x 170mm Mini-ITX Form Factor
- Support Watch dog Technology
- **CPU**
- **Chipset**
- **Memory**
- **Expansion Slots**
- **Power Management**
- Support VIA Nano L2007 (65nm, 1.6GHz)processor
- Front Side Bus 800MHz
- VIA VX900H Chipset
- VIA Chrome9 HD DX9 3D engines (Share System Memory: 64/128/256/512MB)
- 2 * 240-pin DIMM Sockets for un-buffered DDR3 1066MHz SDRAM up to 8GB
- 1 * 32-bit PCI slot
- ACPI S3/S4 Compliant ,supports VIA PowerSaver™ feature

-
- **Storage**
 - **Audio**
 - **Ethernet LAN**
 - **USB**
 - **LVDS**
 - **Rear Panel I / O**
 - **Internal I / O**
 - **BIOS**
 - **Form Factor**
 - **Packing**
 - **Certificate**
 - **Functional**
 - **Temperature**
- 2 * Serial ATA2 3Gb/s connectors with RAID 0,1 function
 - VIA VT1705 HD Audio Code with 6-Channel
 - 2 * RTL8111E 10 / 100 / 1000 PCI-E LAN
 - Embedded 8 * USB 2.0/1.1
 - Onboard 24-bit Single channel LVDS connector
 - 4 * USB 2.0/1.1 ports
 - 1 * PS/2 connector for Keyboard and Mouse
 - 2 * RJ-45 ports
 - 3 * Audio I/O ports (Line-in, Mic and Line-out)
 - 1 * VGA port
 - 1 * DB-9 RS232 COM port
 - 1 * HDMI Connector
 - 1 * CPU Smart Fan Connector, 2 * Sys/Chassis Fan Connectors
 - 2 * USB 2.0/1.1 headers for 4 USB ports
 - 1 * 9-Pin COM Port header
 - 1 * 24 bit Single Channel LVDS header
 - 1 * Parallel header
 - 1 * GPIO header
 - 1 * 24-pin ATX power connector
 - Award 8MB DIP-SPI Flash ROM
 - Mini-ITX Embedded Motherboard(170mmx170mm)
 - Color Box Dimension ■200(W) x 200(D) x 70(H)mm
 - 20 PCS in Cases Gross Weight ■15.4KGS
 - 20 PCS Net Weight ■10.3KGS
 - 20 PCS / Cases, Case size : 720(L) x 410(W) x 200(H)mm
 - CE,FCC,RoHS
 - ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation
 - Operating within 0~60 centigrade
 - Storage within -20-85 centigrade

Product Accessories

- COM cable
- Manual
- CD
- 1x SATA cable
- I/O shield