



249.00 EUR  
 incl. 19% VAT, plus [shipping](#)

- INTEL® Bay Trail-M N2930 SoC Processor (QC, 1.83G)
- INTEL® Bay Trail-I E3827 SoC Processor (DC, 1.75G)
- Support 1 \* DDR3L 1333/1066MHz Single CH up to 4GB
- Support 1 \* Serial ATAll (3Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 2-CH
- 1 \* 24 bits Dual Channel LVDS header
- Support DVI-I Output
- Supports 2 \* Realtek RT8111G Gigabit LAN
- Support CPU Smart FAN
- 148 x 102mm 3.5" SBC Form Factor

<b>CPU</b>	INTEL® Bay Trail-I E3827 SoC Processor (DC, 1.75G)
<b>Chipset</b>	N/A
<b>Memory</b>	1 * DDR3L 1333/1066MHz Single CH SO-DIMM up to 4GB
<b>Expansion Slots</b>	2 * MINI PCI-E (one share with mSATA) socket
<b>Storage</b>	1 * Serial ATAll 3Gb/s connector 1 * mSATA socket
<b>Audio</b>	Realtek ALC662 HD Audio CODEC with 2-Channel
<b>Ethernet LAN</b>	2 * RTL8111G PCI-E Gigabit LAN
<b>USB</b>	Embedded 1 * USB 3.0 + 7 * USB 2.0/1.1
<b>LVDS</b>	Onboard 1 * 24-bits Dual channel LVDS connector
<b>Rear Panel I / O</b>	1 * USB 3.0 port 3 * USB 2.0/1.1 ports 2 * RJ-45 ports 1 * Line-out port 1 * DVI-I port 1 * one-pin 9~24V DC-IN Jack
<b>Internal I / O</b>	2 * USB 2.0 header for 4 * USB 2.0 ports 1 * KB/MS header 1 * Audio header & 1 * HDMI-SPDIF header Chassis Fan Connectors 1 * GPIO header 4 * COM headers (COM1 support RS232/422/485) & 4 * COM ports 5V/12V Selectable headers 1 * chassis intrusion header & 1 * AT mode selectable header
<b>BIOS</b>	AMI 64MB SMT Flash ROM
<b>Form Factor</b>	3.5" SBC form factor (148mmx102mm)

---

<b>Certificate</b>	CE,FCC,RoHS,ERP
<b>Functional</b>	ATM, Automation, Medical Equipment, Security, General Application, Transportation, Digital Signage, Kiosk, POS machine, LCD TV PC, Embedded Fanless application
<b>Temperature</b>	Operating within 0~60 centigrade Storage within -20-85 centigrade