

429.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® Skylake Celeron 3855U/3955U SoC Processor (Default)
- 1* 260-pin Dual-channel DDR4 2133MHz SODIMM Up to 16 GB
- 4/6* 10/100/1000 Base-TX Ethernet Ports
- 1* Full size Mini-SATA Socket (SATA + USB Signal)
- 2* Mini PCIe Slots (1* full size & 1* half size)
- 1* SIM card holder
- Supports on board TPM1.2/2.0 (option)
- 1* RS232 Console, 2* USB3.0
- Supports Antenna up to 4

Processor	- Intel® Skylake Celeron 3855U/3955U SoC Processor (Default)
Chipset	- SoC Integrated
Memory	- 1 * SO-DIMM DDR4-2133MHz up to 16GB
Storage	- 1 * 2.5" SATA3 6Gb/s internal drive bay - 1 * full size mSATA
Network	- 1 * Intel® i219LM GbE & 3 * Intel® i211AT (Default on board) - 2 * Intel® i350 GbE (Expansion by request)
Expansion slot	- 1 * half size Mini PCIe slot (for WiFi expansion) - 1 * full size Mini PCIe slot with 1 * SIM card holder
Front Panel I/O	- 1 * Power LED , 1 * HDD LED - 2 * USB 3.0 - 1 * COM - 4 * RJ45 (3 * i211AT + 1 * i219LM) - 2 * RJ45 (Intel i350 / option)
Rear Panel I/O	- 1 * Power switch - 1 * HDMI (Max. resolution:4096 x 2304@24Hz) - 1 * COM or GPIO (Option) - 1 * DC-in jack - Support Antenna up to 4

Other Features	<ul style="list-style-type: none"> - TPM1.2 or TPM2.0 (On board option) - Reserve internal pin header 8-bit Digital I/O interface (4-in /4-out) - 0~255 segments by software programmable - 1 * System FAN
Power Source	- FSP DC Adapter / AC 90~240V input / DC12V-5A-60W / LV6
Compliance	- CE, FCC, LVD, RoHS
Safety	<ul style="list-style-type: none"> - Vibration test: N.C - Shock test: N.C
Temperature	<ul style="list-style-type: none"> - Operating Temperature: 0 ~ 50° C - Storage Temperature: -10 ~ 70° C
Dimensions	- 232 (W) x 152 (D) x 44 (H) mm
Packing	<ul style="list-style-type: none"> - Net Weight: 1.8KG - Gross Weight: 2.8KG - Color Box dimension: 250 (W) * 115 (D) * 365 (H) mm
OS Support	- 32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux
Warranty	- 1 Year limited warranty