999.00 EUR
incl. 19% VAT, plus shipping

- Intel® Skylake/Kabylake U-series Processor (Default Celeron 3965U)
- 2 * 260-pin Dual-channel DDR4 2133MHz SO-DIMM Up to 32 GB
- 2 * USB2.0, 6 * USB3.0, 1 * COM, 1 * DP, 1 * HDMI, 2 * RJ45,1 * Line-in, 1 * MIC+Line-out Combo
- M/B Form Factor : uTX (117x112mm)
- DC-12V_40W Adapter

MB Model	– JNU792V-3965 uTX _Celeron 3965U Processor	
Part No	VGA	VGA & TPM
	– HBFCU792V-3965-B – HBFCU792VW-3965-B	– HBFCU792V-3965-T – HBFCU792VW-3965-T
BIOS	– AMI 16MB SMT Flash ROM	
CPU/Chipset	– Intel® Skylake/Kabylake U-series Processor (Default Celeron 3965U) Notes : When the system runs, CPU will automatically adjust its working clock frequency according to changing workload.	
Memory	– 2 * 260-pin Dual-channel DDR4 2133MHz SO-DIMM up to 32 GB	
Storage	– 1 * 2.5” SATAIII 6Gb/s internal drive bay – 1 * full-size mSATA/Mini-PCIe shared slot	

Network	– 1 * Intel i211AT GbE, 1 * Intel i219LM GbE – 1 * half-size Mini-PCIe slot (for WiFi model installed)
Rear Panel I/O	– 2 * USB 3.0 ports , 2 * USB 2.0 – 1 * HDMI 1.4 (Max. 4096 x 2304@24Hz resolution) – 2 * RJ45 – 1 * Line-in, 1 * MIC+Line-out Combo (Realtek ALC662VD) – 2 * Antenna holes (WiFi only) – 1 * DC-in jack
Front Panel I/O	– 1 * Power button – 1 * Power LED , 1 * HDD LED – 2 * USB 2.0 , 2 * USB 3.0 – 1 * VGA
Power Source	– FSP AC to DC Adapter / DC12V_3.3A_40W – AC 90~240V input
Compliance	– CE, FCC, LVD, RoHS, ErP Ready
Temperature	– Operating Temperature: 0 ~ 50° C – Storage Temperature: -10 ~ 70° C
Dimensions	– 144 (W) x 116.9 (D) x 65 (H) mm
Packing	– Net Weight: 1.8KG – Gross Weight: 2.8KG – Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm
OS Support	– 32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux
Warranty	– 2 Year limited warranty