999.00 EUR
incl. 19% VAT, plus shipping

- Motorized Pan/Tilt !
- Motorized Zoom !
- POE !
- Web Interface !

Support: Manual [EN] | Software (Windows) | Installation

CTFCAM-1 is an IP-camera with PTZ-support (control camera head left/right, up/down via software) and motorized zoom (control zoom 2.8-12mm via software). The camera is powered via POE-LAN-connector. The camera has a web interface for playback/recording/configuration. She also can be connected to ONVIF compatible video recorders and/or be controlled by ONVIF compatible software.

Specifications :
Image Sensor 1080P: IMX323 + 1/3" NVP2441H
Max. Pixels 1920*1080P
S/N Ratio 50dB(AGC Off)
BNC(HD-TVI/HD-CVI/AHD/CVBS)
LEDs & IR View 4*High Power LED make max 80m IR distance , built in IR-CUT
Lens 4x Optical zoom, (f=2.8-12mm) motorized zoom, Auto Focus
White Balance Auto, ATW, Indoor, Outdoor, Outdoor Auto, Sodium Vapor Lamp Fix/Auto, One-push, Manual
Min. Illumination 0.01Lux @(F1.6,AGC ON) ,0 Lux with IR

Day & Night Auto(ICR) / Color / B/W
Video Compression H.264/MJPEG
S/N Ratio > 50 dB
Bit Rate 32K~16Mbps
Electronic Shutter 1/25-1/100000s
PTZ Mode 4 auto scan, 4 tour, 4 pattern
Network Functions TCP/UDP/HTTP/MULTICAST/UPnP/DHCP/PPPOE/DDNS/NFS/ RTSP
Max Remote Users 128
Operating System Embedded Linux
Pan / Tilt Range Pan: 0°~270, Tilt: 0°~90°, Speed: 30°/sec
Preset 256 Preset (Camera Image Setting)
Protocol PELCO-P, PELCO-D
Working Humidity 0~95%(No condensation)
Working Temperature Outdoor: -35°C~+60°C
Power Supply : POE
Resource Simultaneous remote monitoring, remote operation & local recording