



519.00 EUR incl. 19% VAT, plus shipping

2		
1		
	ĒĒ	
ΞΞ		1.2.2.1.2.
= =	= =	
ΞΞ	EE	
	\	
6	(1)	

Support: <u>Specifications</u>

Jetway OPS player complies with Intel Open Pluggable Specification (OPS) aiming to simplify installation, upgrade and maintenance of large scale digital signage applications, shrinks installation from hours to minutes. OPS101 series is well suited for a wide range of digital signage applications in retail, transport, entertainment, education, and more.

Using Intel® Active Management Technology (Intel® AMT) the OPS player can be remotely powered on and off while offering out-of-band system access. Since Intel® AMT allows the OPS player to be remotely accessed and diagnosed, software issues can be repaired wirelessly while failed hardware components can be identified in advance for preventive maintenance, thus lowering maintenance costs and onsite visits.

- Intel® Kaby Lake I5-7200U (2.5GHz) dual-core processor
- Support 2* DDR4 /2400MHz SO-DIMM Max 32GB
- Support 1* M.2 2242 SSD Socket and 1* SATA3 Connector
- Support 1* M.2 1630 or 2230 for WIFI
- Intel® I219LM Gigabit LAN
- 1* JAE 80pin Connector (1* HDMI2.0, 1* USB3.0, 1* USB2.0, 1* TX/RX, 1* Power Button, 1* DC-in)
- 2* USB3.0, 2* USB2.0, 1*HDMI1.4b, 1* Line-Out, MIC, 1* IR
- 12~19V DC-in



MB Model	- JNC9C-OPS7200 (EPIC Size)
Part No	– OPS101-7200
CPU/Chipset	– Intel® Kaby Lake-U I5-7200 2.5GHz Dual core
Memory	– 2 * DDR4 SO-DIMM up to 32GB
Expansion Slot	– 1 * M.2 2230 connector
Storage	– 1 * Serial ATA3 6Gb/s connector
	– 1 * M.2 2242 connector for SSD
Audio	– ALC662 Audio CODEC
	- HD Audio CODEC
Network	– 1 * INTEL® I219LM Chip
	- 10/100/1000 Base-T Ethernet
	– 1 * RJ45
	– 1 * HDMI1.4b (Support 4096*2304@24Hz)
	- 1 * Line-out + MIC
	– 2 * USB3.0
Rear Panel I/O	– 2 * USB2.0
	– 1 * IR
	– 1 * Power Button, 1 * Reset Button
	– 1 * Power LED, HDD LED
	- 2 * WIFI Antenna
JAE Connector	– 1 * HDMI2.0 (Support 4096*2160@60Hz)
	– 1 * USB3.0
	– 1 * USB2.0
	– 1 * RX/TX
	– 1 * Power Switch
	– 1 * DC-in
Power Source	– DC 12~19V
Compliance	- RoHS, ErP Ready
Temperature	– Operating Temperature: -10 ~ 60° C
	- Storage Temperature: -20 ~ 65° C
Dimensions	– 202 (W) x 118 (D) x 30 (H) mm
OS Support	- Windows 10, Linux
Warranty	– 1 Year limited warranty