



98.00 EUR

incl. 19% VAT, plus [shipping](#)

- Rev AF0 DFI-ITOX
- LGA1150
- Intel C226

- Intel® Xeon®/Core™ 4. Gen., Intel® C226 Chipsatz
- Dual channel DDR3 1600MHz DIMM up to 32GB
- 1 HDMI, 1 DVI-I
- Multiple expansion: 2 PCIe x16 (1 x16 or 2 x8 signal), 2 PCIe x4 (1 x4 and 1 x1 signal), 3 PCI, 6 SATA 3.0
- Rich I/O: 2 Intel GbE, 10 USB, 6 COM

Processor	<p>4th Generation Intel® Core™ processors, LGA 1150 socket</p> <p>Intel® Xeon® E3-1275 v3 Processor, 8M Cache, 3.9 GHz, 95W</p> <p>Intel® Xeon® E3-1268L v3 Processor, 8M Cache, 3.3 GHz, 45W</p> <p>Intel® Xeon® E3-1225 v3 Processor, 8M Cache, 3.6 GHz, 95W</p> <p>Intel® Core™ i7-4770S Processor, 8M Cache, 3.9 GHz, 65W</p> <p>Intel® Core™ i7-4770TE Processor, 8M Cache, 3.3 GHz, 45W</p> <p>Intel® Core™ i5-4590S Processor, 6M Cache, 3.7 GHz, 65W</p> <p>Intel® Core™ i5-4590T Processor, 6M Cache, 3.0 GHz, 35W</p> <p>Intel® Core™ i5-4570S Processor, 6M Cache, 3.6 GHz, 65W</p> <p>Intel® Core™ i5-4570TE Processor, 4M Cache, 3.3 GHz, 35W</p> <p>Intel® Core™ i3-4360 Processor, 4M Cache, 3.7 GHz, 54W</p> <p>Intel® Core™ i3-4350T Processor, 4M Cache, 3.1 GHz, 35W</p> <p>Intel® Core™ i3-4340TE Processor, 4M Cache, 2.6 GHz, 35W</p> <p>Intel® Core™ i3-4330 Processor, 4M Cache, 3.5 GHz, 54W</p> <p>Intel® Core™ i3-4330TE Processor, 4M Cache, 2.4 GHz, 35W</p> <p>Intel® Pentium® G3420 Processor, 3M Cache, 3.2 GHz, 53W</p> <p>Intel® Pentium® G3320TE Processor, 3M Cache, 2.3 GHz, 35W</p> <p>Intel® Celeron® G1820 Processor, 2M Cache, 2.7 GHz, 53W</p> <p>Intel® Celeron® G1820TE Processor, 2M Cache, 2.2 GHz, 35W</p>
Chipset	Intel® C226 Chipset

Memory	Four 240-pin ECC DIMM up to 32GB Dual Channel DDR3 1333/1600MHz
BIOS	AMI SPI 64Mbit
Graphics	Intel® HD Graphics (Open GL 4.0, DirectX 11.1)
Displaysupport:	1x HDMI (resolution up to 4096x2304 @ 24Hz or 2560x1600 @ 60Hz) 1x DVI-I (resolution up to 1920x1200 @ 60Hz)
Expansion	2 x PCIe x16 (1 x16 or 2 x8 signal) 2 x PCIe x4 (1 x4 and 1 x1 signal) 3 x PCI 6 x SATA 3.0
Audio	Realtek ALC886
Ethernet	1 x Intel® I210 PCIe (10/100/1000Mbps) 1 x Intel® I217LM with iAMT9.0 (10/100/1000Mbps)
Rear I/O	2 x GbE (RJ-45) 2 x RS-232/422/485 (RS-232 w/ power) (DB-9) 4 x USB 3.0 2 x USB 2.0 1x PS/2 1x HDMI 1x DVI-I 1x Line Out 1x Mic In 1x Line In
Internal I/O	4 x RS232 (2.0mm pitch) 4x USB 2.0 1 x Audio (Line-out/Mic-in) 1 x S/PDIF 6x SATA 3.0 RAIS 0/1/5/10 1x 8-bit DIO 1x LPC
Watchdog Timer	System Reset, Programmable via Software from 1 to 255 Seconds
Power	ATX - 8pin ATX 12V power / 24-pin ATX Power Consumption: 75.07W with E3-1275 v3 at 3.50GHz and 4x 2GB DDR3 DIMM
OS Support:	Windows 7 Ultimate x86 & SP1 (32-bit) Windows 7 Ultimate x64 & SP1 (64-bit) Windows 8 Enterprise x86 (32-bit) Windows 8 Enterprise x64 (64-bit) Windows 10 IoT Enterprise (64-bit)
Enviroment	Temperatur: Operating: 0 to 60°C Storage: -20 to 85°C Humidity: Operating: 5 to 90% RH Storage: 5 to 90% RH
Dimensions:	ATX form factor 305mm (12") x 244mm (9.6")
Packing List	1 DL3631 motherboard 1 Serial ATA data cable (Length: 500mm, w/lock) 1 I/O shield