

CARTET.COM

999.00 EUR

incl. 19% VAT, plus shipping

- For Celeron M 1.5Ghz
- FANLESS carpc system
- Integr. Autostart Controller
- Dualchannel VGA

Support: 🔁 Assembling Tutorial [DE] | 🔁 Assembling Tutorial [EN] | 🔁 Dual-Out-HowTo [EN]

Fanless CarPC-barebone for use with Intel P4/Celeron M CPU. Celeron-M 1.7Ghz is recommeded for fanless operation.

The CALU-M(2)C-Series has an integrated car-power supply (direct connectable to car battery and ignition plus + integrated automatic Start/Stop-Controller.

The time intervals for automatic Start and Stop can be adjusted in the BIOS of the PC !

CALU specifications	
Processor (supported)	Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher
Memory	Supports DDR 333/266 DIMM RAM
	0.8" low profile
	2x memory slots !
	Maximum : 2 GB
Video	Intel Extreme Graphics 2
	Supports up to 64MB DVMT video memory
Audio	Software AC '97 Audio CODEC



[http://www.cartft.com/catalog/il/365]

Peripheral Connection	Front :	
	1 x IEEE 1394 Firewire port	
	1 x USB 2.0 / 1.1 Port	
	1 x MIC Port	
	1 x Ear Phone output Jack	
	Power-on button	
	Reset button	
	Power-on and HDD LED	
	Rear :	
	1 x RS232 COM port	
	1 x RJ45 10/100Mb Fast Ethernet	
	1 x Line-Out output Jack	
	2 x USB 2.0 / 1.1 Ports	
	1 x 15 pin VGA	
	1 x DVI	
Storage	One 2.5 inch Hard Disk and 9.5mm high.	
	(Support Ultra DMA 33/66/100).	
Weight & Size	System approximately 3kg (fully equipped).	
	System Dimension: 155 x 255 x 55 mm	
_		
Power req.	9-16VDC, 5A	
Accessory		
Storage	Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo	
	Supports all 2.5" standard IDE hard drive, ATA-100/66/33.	
Scope of supply	Connector cable for Plus, ignition plus and ground	
	Barebone	
	Barebone	
	CPU Kühlkörper	

Installation Tutorial : Support / Manuals

Graphics driver for 800x480 resolution : Here