



999.00 EUR
incl. 19% VAT, plus [shipping](#)

- Fanless !
- LVDS

Processor 800MHz
- VIA C3/ VIA Eden EPGA processor

Chipset
- VIA CN400 North Bridge
- VIA VT8237 South Bridge

System Memory
- 1 DDR266/333/400 DIMM socket
- Up to 1GB memory size

VGA
- Integrated VIA UniChrome Pro AGP graphics with MPEG-2 decoder
/MPEG-4 Accelerator

Expansion Slots
- 1 PCI

Onboard IDE
- 2 X UltraDMA 133/100 Connector

Onboard Serial ATA
- 2 SATA Connectors

Onboard LAN
- VIA VT6103 10/100 Base-T Ethernet PHY

Onboard Audio
- VIA VT1617A 6channel AC' 97 codec

Onboard TV Out
- VIA VT1623 TV Encoder

Onboard 1394
- VIA VT6307S IEEE 1394 Firewire

Back Panel I/O

- 1 PS2 mouse port
- 1 PS2 keyboard port
- 1 RJ-45 LAN port
- 1 Serial port
- 2 USB 2.0 ports
- 1 VGA port
- 1 PCA port (SPDIF or TV out)
- 1 S-video port
- 3 Audio jacks: line-out, line-in and mic-in (Smart 5.1 Support)

Onboard I/O Connectors

- 3 USB connector for 6 additional USB 2.0 ports
- 1 1394 connector for 1 1394 port
- 1 Serial port connector for a second com port
- 1 VIP connector
- 1 Front-panel audio connector (Mic-in and Line-out)
- 1 CD audio-in connector
- 1 FIR connector
- 1 CIR connector (Switchable for KB/MS)
- 1 LPT port connector
- 1 Wake-on-LAN connector
- 2 Fan connectors: CPU/Sys FAN
- 1 I2C connector
- 1 LVDS/TTL module connector (Optional)
- 1 +12V power connector
- ATX power connector

BIOS

- Award BIOS
- 4/8Mbit flash memory

System Monitoring & Management

- CPU voltage monitoring
- Wake-on-LAN, Keyboard Power-on, Timer Power-on
- System power management
- AC power failure recovery

Operating Temperature 0~50°C

Operating Humidity 0% ~ 93% (relative humidity, non-condensing)

Form Factor

- Mini-ITX (6 layer)
- 17 cm x 17 cm