



999.00 EUR

incl. 19% VAT, plus shipping

- FANLESS carpc system
- Core2Duo
- Integr. Automotive power
- Intel 945 chipset

Support: Assembling Tutorial [DE] | Assembling Tutorial [EN]

Fanless CarPC-barebone for use with Intel Celeron M440 CPU.

The CALUCORE-M(2)C-Series has an integrated car-power supply (direct connectable to car battery and ignition plus + integrated automatic Start/Stop-Controller.

The time intervals for automatic Start and Stop can be adjusted in the BIOS of the PC !

CALU specifications	
Processor (supported)	Support Socket 479, FSB 533MHZ, FSB 667MHZ, Intel Mobil CPU (Celeron M 410, 420, 430, 440 & 450 CPU, Core
	Duo T2300, T2400, T2500, T2600 & T2700 CPU, Core 2 Duo T5500, T5600, T7200, T7400 & T7600 CPU).
Memory	Support 1x SO-DDR-II RAM
Chipset	Intel Intel 945GM / ICH 7M
Video	Intel Graphics Media Accelerator 950
Audio	Software AC '97 Audio CODEC
Peripheral Connection	Front :
	1 x IEEE 1394 Firewire port
	1 x USB 2.0 / 1.1 Port
	1 x MIC Port
	1 x Ear Phone output Jack
	Power-on button
	Reset button
	Power-on and HDD LED
	Rear :
	1 x RS232 COM port
	1 x RJ45 10/100/1000 Mbit Fast Ethernet
	1 x Line-Out output Jack
	2 x USB 2.0 / 1.1 Ports
	1 x 15 pin VGA
	1 x 12v DC Power Jack input
Storage	One 2.5 inch SATA Hard Disk
	(Support Ultra DMA 33/66/100).
Weight & Size	System approximately 3kg (fully equipped).
	System Dimension: 155 x 255 x 55 mm



Power req.	9-16VDC, 5A
Accessory	
Storage	Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo
	Supports all 2.5" SATA IDE hard drive, ATA-100/66/33.
Scope of supply	Connector cable for Plus, ignition plus and ground
	Barebone
	CPU Kühlkörper

Graphics driver for 800x480 resolution : Here